

Supporting Drilling Information to Alacer Gold Announcement

This document provides supporting drill collar locations and composite assay results for the Çöpler Saddle drilling program referenced in the announcement “Alacer Gold Reports Exploration Results from the Çöpler Saddle Shear Zone at the Çöpler Gold Mine”, dated September 26, 2019.

Drill collar locations are surveyed in UTM Zone 37N, ED50 grid using differential GPS in units of meters. All drilling was diamond core drilling with HQ and PQ core sizes. HQ is 63.5mm and PQ is 85mm in diameter.

Drill Collar Coordinates

Hole_ID	Easting	Northing	Elevation	Azimuth	Dip	End of Hole (m)
CDD652	457863.4	4363470.7	1360.2	270	-45	57.6
CDD653	457865.1	4363471.7	1360.1	280	-60	80.4
CDD654	457863.2	4363486.0	1360.0	270	-45	113.2
CDD655	457881.0	4363517.8	1360.4	0	-60	60.0
CDD656	457865.1	4363513.6	1360.0	300	-45	74.2
CDD657	457865.6	4363515.1	1360.3	310	-60	57.0
CDD658	457774.4	4363558.5	1446.8	120	-60	258.3
CDD659	457919.0	4363519.5	1360.1	335	-60	125.5
CDD660	457921.7	4363522.2	1360.0	50	-50	107.2
CDD661	457869.7	4363578.9	1405.2	85	-63	213.8
CDD662	457973.7	4363609.3	1380.2	90	-60	108.0
CDD663	457945.2	4363524.3	1360.0	330	-45	100.0
CDD664	457944.3	4363523.7	1360.0	315	-55	101.4
CDD665	457978.4	4363564.5	1366.9	330	-65	102.0
CDD709	458012.2	4363512.8	1364.5	315	-55	240.5
CDD717	458040.5	4363546.3	1365.3	303	-57	308.0
CDD718	457937.4	4363480.9	1365.2	327	-50	179.0
CDD719	457970.0	4363499.0	1366.7	320	-55	240.4
CDD720	457999.2	4363705.4	1389.3	100	-70	164.1
CDD721	458017.1	4363577.6	1372.7	305	-60	83.5
CDD721A	458015.0	4363578.9	1373.2	305	-60	260.6
CDD725	457772.1	4363312.6	1437.0	130	-60	53.2
CDD726	457770.9	4363313.3	1437.1	150	-70	50.4
CDD728	457746.0	4363175.5	1445.5	100	-60	75.5
CDD729	457745.1	4363174.3	1445.6	290	-50	73.8
CDD731	457773.4	4363310.9	1437.0	70	-60	32.0
CDD731A	457773.1	4363310.8	1436.8	75	-60	45.5
CDD733	457747.8	4363117.3	1446.0	290	-50	93.5
CDD735	457749.2	4363117.6	1445.7	90	-60	67.5
CDD737	457720.4	4363251.0	1455.4	90	-60	63.5
CDD745	457995.0	4363573.3	1373.0	305	-58	237.6
CDD746	457985.8	4363591.3	1379.6	0	-90	106.7
CDD749	458032.8	4363600.8	1373.8	0	-90	90.6
CDD750	457696.5	4363165.2	1467.1	120	-50	87.5
CDD773	457448.4	4362526.1	1614.0	110	-60	112.9
CDD774	457441.0	4362441.8	1626.8	110	-60	121.0

CDD775	457561.4	4362497.0	1619.3	0	-90	89.6
CDD776	457536.3	4362403.1	1642.4	260	-60	148.0
CDD777	457543.1	4362567.6	1581.1	0	-90	175.0
CDD786	457384.2	4362413.7	1620.7	130	-60	115.0
CDD787	457391.6	4362477.0	1620.7	150	-60	86.0
CDD788	457398.1	4362525.9	1620.7	110	-60	104.5
CDD789	457436.4	4362490.0	1618.7	110	-60	136.5
CDD790	457541.6	4362567.1	1580.6	270	-60	115.0
CDD791	457286.1	4362450.1	1607.2	120	-60	202.0
CDD795	457397.7	4362504.9	1621.2	110	-60	98.3
CDD796	457406.1	4362502.5	1620.6	110	-60	154.7
CDD798	457403.9	4362432.7	1624.3	110	-60	125.5
CDD809	457501.7	4363956.8	1454.5	70	-50	139.0
CDD810	457541.1	4363959.5	1459.8	45	-50	115.0

Çöpler Saddle Drill Intercepts

Hole ID	From (m)	To (m)	Interval (m)	Au g/t	Remarks	Depth (m)	Comments	
CDD652	13	16	3	0.59	Sulfide	57.6		
CDD653	-	-	-	-	-	80.4	No Significant Interval	
CDD654	0	12	12	0.55	Mixed	113.2	50/50 Oxide Sulfide	
	73	95	22	1.41	Oxide			
<i>including</i>	80	82	2	7.06	Oxide			
	100	104	4	0.39	Oxide			
CDD655	4	11	7	0.34	Sulfide	60		
	18.3	21.3	3	0.32	Sulfide			
	28.1	33.6	5.5	3.88	Mixed		67/33 Oxide Sulfide Ratio	
<i>including</i>	29.1	29.8	0.7	9.35	Oxide			
<i>including</i>	31.6	32.6	1	5.76	Oxide			
	51.6	57.6	6	0.49	Oxide			
CDD656	0	31.1	31.1	1.26	Mixed	74.2	68/32 Oxide Sulfide Ratio	
<i>including</i>	23	24	1	14.8	Oxide			
CDD657	0	9	9	2.84	Mixed	57	22/78 Oxide Sulfide Ratio	
	24.5	47.1	22.6	9.65	Oxide		Includes isolated intervals of core loss totaling 0.5m.	
	<i>including</i>	26.2	32.2	6	30.78		Oxide	
	<i>including</i>	28.2	29.2	1	104		Oxide	
	<i>including</i>	36.2	37.6	1.4	8.6		Oxide	
CDD658	65.5	68.5	3	0.74	Oxide	258.3		
	83.1	86.1	3	0.31	Oxide			
	159.7	162.8	3	0.85	Oxide			
	234.5	239.5	5	0.68	Oxide			
	242.5	245.5	3	1.15	Mixed		67/33 Oxide Sulfide Ratio	
CDD659	0	5	5	0.55	Sulfide	125.5		
	35	52	17	8.41	Mixed		82/18 Oxide Sulfide Ratio	
	<i>including</i>	36	37	1	5.32		Oxide	
	<i>including</i>	43	50	7	18.7		Oxide	
		80	84	4	0.48		Oxide	
	111.5	113.5	2	1.4	Oxide			
CDD660	0	15	15	1.09	Sulfide	107.2		
<i>including</i>	0	1	1	7.26	Sulfide			
	76	81	5	0.42	Sulfide			
CDD661	157	160	3	0.6	Oxide	213.8		
	166	167.1	1.1	1.41	Oxide			
	170.7	184	13.3	2.13	Mixed		Includes isolated intervals of core loss totaling 0.9m. 84/16 Oxide Sulfide Ratio	
	188	192	4	0.39	Sulfide			
CDD662	96	98	2	4.19	Oxide	108		
<i>including</i>	96	97	1	5.35	Oxide			
CDD663	7	25	18	2.14	Mixed	100	6/94 Oxide Sulfide Ratio	
<i>including</i>	8	11	3	10.13	Sulfide			
	35.2	49.7	14.5	0.83	Mixed		94/6 Oxide Sulfide Ratio	

Hole ID	From (m)	To (m)	Interval (m)	Au g/t	Remarks	Depth (m)	Comments
	61.7	76.8	15.1	0.86	Oxide		Includes isolated intervals of core loss totaling 1.5m
CDD664	9.5	20.5	11	0.47	Sulfide	101.4	
	49	63	14	7.49	Oxide		
	including 54	62	8	12.25	Oxide		
	74	78	4	0.44	Oxide		
	82	88	6	0.81	Oxide		
CDD665	66.6	67.8	1.2	3.36	Oxide	102	
CDD709	17.5	21.5	4	0.59	Sulfide	240.5	
	149.2	157.5	8.3	0.33	Sulfide		Includes isolated intervals of core loss totaling 3.3m
	164	174.6	10.6	2.52	Mixed		Includes isolated intervals of core loss totaling 0.9m. 21/79 Oxide Sulfide Ratio
	including 173.7	174.6	0.9	20.3	Oxide		
	190.3	194	3.7	0.88	Oxide		
	197	229.7	32.7	2.25	Oxide		
	including 209.5	210.5	1	5.43	Oxide		
CDD717	32.5	39.5	7	0.88	Mixed	308	14/86 Oxide Sulfide Ratio
	125	130	5	0.41	Sulfide		
	174.5	182.5	8	0.53	Sulfide		
	185.5	206.9	21.4	1.27	Mixed		29/71 Oxide Sulfide Ratio
	231.2	249.2	18	0.79	Oxide		
	254.2	279.7	26.5	1.83	Mixed		85/15 Oxide Sulfide Ratio
	including 267.7	268.7	1	25.7	Oxide		
	285	296.5	11.5	1.32	Oxide		
	299.5	308	8.5	2.93	Oxide		
including 300.6	301.6	1	7.91	Oxide			
CDD718	42.2	48.2	6	0.71	Sulfide	179	
	96.3	107.7	11.4	3.87	Mixed		77/23 Oxide Sulfide Ratio
	including 102.9	104.9	2	18.13	Oxide		
	110.6	118.6	8	0.3	Oxide		
	147.5	155.1	7.6	0.44	Oxide		
CDD719	95.1	108.5	13.4	1.16	Sulfide	232.9	
	120.7	161.5	40.8	4.74	Mixed		80/20 Oxide Sulfide Ratio
	including 129.8	133.1	3.3	6.94	Oxide		
	including 137.1	141.5	4.4	25.78	Oxide		
CDD720	-	-	-	-	-	164.1	No Significant Interval
CDD721	74	75.5	1.5	1.35	Oxide	83.5	
	79.6	83.5	3.9	1.13	Oxide		
CDD721A	83.1	93	9.9	1.08	Oxide	260.6	Includes isolated intervals of core loss totaling 1m
	including 85.1	86.1	1	5.01	Oxide		
	134	139	5	0.46	Oxide		
	154.9	187.8	32.9	1.03	Oxide		Includes isolated intervals of core loss totaling 1.2m
CDD725	31.3	36.5	5.2	0.73	Oxide	53.2	

Hole ID	From (m)	To (m)	Interval (m)	Au g/t	Remarks	Depth (m)	Comments	
CDD726	10.8	14	3.2	0.49	Oxide	50.4		
CDD728	55.5	57.2	1.7	4.69	Oxide	75.5		
<i>including</i>	55.5	56.3	0.8	9.35	Oxide			
CDD729	23	34.1	11.1	8.85	Mixed	73.8	89/11 Oxide Sulfide Ratio	
<i>including</i>	24.2	25.2	1	11.55	Oxide			
<i>including</i>	26.2	30.1	3.9	15.879	Oxide			
<i>including</i>	31.1	32.1	1	8.36	Oxide			
CDD731	-	-	-	-	-	32	No Significant Interval. Abandoned at 32m and re-drilled as CDD731A	
CDD731A	24	28.8	4.8	1.57	Oxide	45.5		
CDD733	-	-	-	-	-	93.5	No Significant Interval	
CDD735	34.4	40.1	5.7	39.45	Mixed	67.5	75/25 Oxide Sulfide Ratio	
<i>including</i>	37.7	39.1	1.4	155.5	Sulfide			
	47	49.2	2.2	7.74	Mixed			
<i>including</i>	48.1	49.2	1.1	14.6	Sulfide			
CDD737	20	22.6	2.6	2.96	Oxide	63.5		
<i>including</i>	21.8	22.6	0.8	8.05	Oxide			
CDD745	117.6	120.6	3	0.42	Oxide	237.6		
CDD746	60	61	1	1.96	Oxide	106.7		
	64	85.5	21.5	0.88	Mixed		40/60 Oxide Sulfide Ratio	
<i>including</i>	65.2	66.2	1	7.38	Oxide			
CDD749	67.4	71.5	4.1	1.23	Mixed	90.6	22/78 Oxide Sulfide Ratio	
	76.2	88.2	12	0.42	Mixed		8/92 Oxide Sulfide Ratio	
CD750	9.4	12.4	3	1.01	Oxide	87.5		
	40.4	43.7	3.3	0.37	Oxide			
CDD773	59.6	64.6	5	1.83	Oxide	112.9		
	69.6	77.8	8.2	4.35	Oxide			
	<i>including</i>	73	73.8	0.8	38		Oxide	
CDD774	40.4	47.5	7.1	6.08	Oxide	121		
<i>including</i>	44.9	46.5	1.6	17.25	Oxide			
	104.3	112.3	8	0.3	Mixed		63/37 Oxide Sulfide Ratio	
CDD775	-	-	-	-	-	89.6	No Significant Interval	
CDD776	85.5	86.5	1	1.08	Oxide	148		
	134.7	135.6	0.9	5.85	Oxide			
CDD777	39.8	40.8	1	2.03	Sulfide	175		
CDD786	55.8	58.8	3	0.63	Sulfide	115		
	65.6	73.5	7.8	7.2	Oxide			
	<i>including</i>	69.8	71.5	1.7	27.66		Oxide	
		78	89.3	11.3	4.33		Oxide	
	<i>including</i>	78	79	1	8.54		Oxide	
	<i>including</i>	84	85	1	5.37		Oxide	
	<i>including</i>	87.4	89.3	1.9	13.89		Oxide	
	106	111	5	0.45	Mixed	60/40 Oxide Sulfide Ratio		
CDD787	46	49	3	0.48	Oxide	86		
	57	58	1	1.38	Oxide			
	64.3	72.3	8	0.44	Sulfide			

Hole ID	From (m)	To (m)	Interval (m)	Au g/t	Remarks	Depth (m)	Comments
	75.3	78.3	3	0.53	Mixed		33/67 Oxide Sulfide Ratio
	82.3	86	3.7	1.04	Sulfide		22/78 Oxide Sulfide Ratio
CDD788	89.2	90.2	1	2.32	Sulfide	104.5	
	96.7	103.4	6.7	1.33	Sulfide		15/85 Oxide Sulfide Ratio
CDD789	10	11	1	2	Oxide	136.5	
	45.1	58.8	13.7	0.41	Oxide		
	64	76	12	0.46	Oxide		
	93	100	7	2.93	Oxide		
<i>including</i>	96	97	1	16.1	Oxide		
CDD790	0	4	4	2.23	Oxide	115	
	75.4	79.8	4.4	1	Mixed		75/25 Oxide Sulfide Ratio
CDD791	-	-	-	-	-	202	No Significant Interval
CDD795	48	50	2	2.13	Oxide	98.3	
	85	95	10	0.63	Sulfide		20/80 Oxide Sulfide Ratio
CDD796	85	88	3	1.29	Mixed	154.7	67/33 Oxide Sulfide Ratio
	93	99.2	6.2	0.67	Oxide		
	109	113.5	4.5	0.32	Oxide		
	128.9	131.7	2.8	0.84	Oxide		
CDD798	46.6	50.9	4.3	1.17	Mixed	125.5	70/30 Oxide Sulfide Ratio
	82	85	3	0.63	Oxide		
	91	96.8	5.8	1.15	Oxide		
	115.6	117.6	2	1.31	Sulfide		
CDD809	92.7	94.7	2	1.27	Oxide	138	
CDD810	106.9	111.6	4.7	0.41	Oxide	115	